IMPROVEMENT OF OIL RECOVERY OF THE FLOODED LAYERS AT FORMATION HYDRAULIC FRACTURING

T. Yu. Yusifov, S. G. Panyak, A. A. Askerov, Yu. M. Varvaruk, M. Yu. Yusifova

« - », «Global Energy», «ASKON Azticar t» MMC . ; (); (); (); (); ()

Key words: *formation hydraulic fracturing (FHF); injected waters front; injected waters static front; dynamic front; influence of the injected waters front on FHF efficiency; reservoir pressure maintenance*

(. 1).

().

(. 2).

. 2.

1. — // — 2011. — 5. — . 56-59.
2. — , 2004.
3. — // — 2014. — 4. — . 38-42.
4. // XIV «» . — , 23–25 2014 . — . 48.
5. ») // . — 2012. — 3. — . 179-184. (« -
6. — (14 « -
7. ») // . — 2012. — 2. — . 182-188.
- // V : «» . // . — , 2015.

Information about the author

- Yusifov T. Yu.**, Candidate of Science in Engineering, chief specialist of LLC «Rosneft — Ufa Research and Designing Institute», Ufa, phone: 89373087202, e-mail: Yusifov-TY@ufanipi.ru
- Panyak S. G.**, Doctor of Geology and Mineralogy, head of the chair of geology, the Ural State Mining University, phone: 8(343)2574105, e-mail: panjaks@rambler.ru
- Askerov A. A.**, postgraduate, the Ural State Mining University, phone: 8(34936)57539, e-mail: Askerov.A.M@mail.ru
- Varvaruk Yu. M.**, president of «Global Energy Abesheron Operating Company», Baku, Republic of Azerbaijan, phone: 89170480273, e-mail: YVarvaruk@AOC.az
- Yusifova M. Yu.**, engineer of «ASKON Azticar t» MMC, Baku, Republic of Azerbaijan, phone: 89170480273, e-mail: YusifovTY@ufanipi.ru